

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):


- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61B	A2	(11) International Publication Number: WO 97/10743 (43) International Publication Date: 27 March 1997 (27.03.97)
(21) International Application Number: PCT/IB96/01298 (22) International Filing Date: 17 September 1996 (17.09.96) (30) Priority Data: 08/531,780 21 September 1995 (21.09.95) US (71) Applicant: MEDICINELODGE, INC. [US/US]; 152 South 600 West, Logan, UT 84321 (US). (72) Inventors: CHERVITZ, Alan; 152 South 600 West, Logan, UT 84321 (US). GOBLE, E., Marlowe; 850 East 1200 North, Logan, UT 84341 (US). (74) Agent: RUSSELL, M., Reid; Suite 300, 261 East 300 South, Salt Lake City, UT 84111 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: SUTURE ANCHOR SYSTEM AND METHOD (57) Abstract <p>A suture anchor system and procedure for securing a suture, into and to extend from a bone cortex surface. The system includes forming a hole into a bone cortex surface that is of a diameter and depth to provide a wall surface area that is at least as great as the surface area of an end section of a suture or sutures fitted therein, and, by filling the hole with an adhesive that is allowed to cure, a suture mounting is provided that will have a pullout strength or purchase that is greater than a load as is anticipated to be applied thereto when the suture is used to connect a ligament, or the like, to the bone. To increase which purchase a portion of the hole formed into the bone cortex may be counter bored to form an outwardly extending shirt area to increase the hole wall surface area, the suture may be folded upon itself and the fold fitted into the formed hole, a knot may be tied in the suture end, or a pair or more of sutures can be combined together that can also be folded and a knot tied therein, for increasing the area of the suture that is for fitting in the formed hole, which hole containing the suture or sutures is then filled with an adhesive material, that, when cured, completes the suture mounting to the bone cortex. The invention further includes the steps for practicing the suture mounting system.</p> 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

SUTURE ANCHOR SYSTEM AND METHOD

S P E C I F I C A T I O NBACKGROUND OF THE INVENTIONField of the Invention

This invention relates to medical equipment and in particular to devices and methods for securing a suture to a bone for use in maintaining a section of a ligament or soft tissue thereto.

Prior Art

Devices and methods for positioning and securing an anchor, fastener or the like to a bone to secure a suture thereto that is used to fasten a section of a ligament, or the like, are well known. A number of earlier inventions of one or both of the present inventors show several different suture anchor arrangements and drivers. For example, one such a driver mounting a suture anchor wherefrom a suture extends that is for turning the anchor into a bone is shown in a U.S. Patent to E. Marlowe Goble, No. 4,632,100. Also, other driver and suture anchor combinations of one or both of the present inventors, U.S. Patent No's. 5,411,506 and 5,411,523, have provided for turning an anchor whereto a suture is connected into a bone for use in mounting a ligament, or the like, to that bone. Further, other patents to one of the present inventors, U.S. Patent No.'s 4,738,255, 5,013,316 and 5,141,520, illustrate other driver and anchor combinations and ligament mounting arrangements are shown in U.S. Patent No's

4,772,286 and Re. 34,293, 4,870,957, 4,927,421, 4,997,433, 5,129,902, 5,352,229. Unlike these earlier suture anchor and driver combinations, however, the present invention provides for seating and mounting a suture directly into a hole drilled or otherwise formed into a bone without a need to use a separate anchor or driver.

A number of combinations of anchors, some of which include arrangements for capturing, maintaining and fitting sutures to extend from seated anchors are shown in U.S. Patents issued to others, No.'s 4,779,616; 4,946,468; 5,071,420; 5,100,417; 5,102,421; 5,139,520; 5,207,679; 5,211,650; 5,224,946; 5,236,445; and 5,258,016. None of these patents, however, provide for a direct mounting of a suture into a bone material that are like the arrangement of the invention that provides a simple and easily practiced system and process for rapidly and reliably mounting a suture to a location on or into a bone surface.

SUMMARY OF THE INVENTION

It is therefore a principal object of the present invention in a suture anchor system and procedure to provide for mounting a suture to a selected location in a bone cortex for connecting a ligament, or the like, thereto.

Another object of the present invention is to provide a suture anchor system that can be a single suture strand, or multiple suture strands and with or without a knot formed in the end thereof, with the suture strand or strands end for

fitting in a hole that has been formed into a bone to receive an adhesive to encapsulate the suture or sutures end within the hole, mounting it therein.

Another object of the present invention is to provide a suture anchor system that may be a single suture or multiple sutures that are wound, braided, or otherwise maintained together, for fitting into a hole that is formed into a bone cortex so as to provide a hole wall area and depth relationship to the suture or sutures cross section and length of a suture section for fitting into and bond in which hole when the hole is filled with a particular adhesive.

Another object of the present invention is to provide for filling the formed hole with the adhesive that will, when cured, encapsulate the suture or sutures therein, bonding to the hole wall and suture or sutures to permanently mount the suture or sutures therein, with portion or portions of the suture or sutures extending from the bone surface for attachment to a ligament, or the like.

Another object of the present invention is to provide a suture anchor system that, to increase pullout strength of an anchored suture, a single suture or plurality of sutures ends that are for fitting into the bone hole are knotted and receive an adhesive in that bone hole that, when dried, bonds to both the hole wall and knotted suture or sutures, the knot or knots to add additional pullout strength over a suture or sutures without such knotted end.

Still another object of the present invention is to provide a suture anchor system where, to increase pullout strength of an anchored suture, the bone hole is formed to have an outwardly sloping skirt portion, increasing the hole interior surface area.

Still another object of the present invention is to provide a process for securing a suture or sutures to a bone cortex where a hole is drilled into a bone material that is of a determined width and depth to receive an end portion a suture or sutures fitted therein and receive an adhesive to encapsulate the suture or sutures end portion or portions and bond thereto and to the bone hole wall surface prohibiting the suture or sutures end portion or portions from being pulled therefrom when an anticipated or greater tensile force is applied to the suture or sutures.

Still another object of the present invention is to provide a suture or sutures end portion or portions mounting that is simple and reliable to use for mounting a suture or sutures to a bone cortex surface, with the suture or sutures then used for attaching to a ligament, or the like.

In accordance with the above objects, the present invention is in a suture anchor system and process for mounting a suture or sutures into, so as to extend from, a bone material surface for attachment to a ligament, or the like. The system includes a single suture or a number of sutures that may be wound, braided, or otherwise maintained together, with an end

portion or portions of the suture or sutures for fitting into a hole that has been formed through a bone cortex surface and into the bone material. The hole is formed to have a diameter and depth such that, with the suture or sutures end portion or portions fitted therein, and with an introduction of an adhesive or resin therein, and after adhesive or resin drying, curing or polymerizing, the suture end portion or portions will be secured within the hole, resisting withdrawal when a tensile stress is applied thereto. The suture or sutures end portion or portions can be knotted and fitted within the prepared hole to increase suture surface area, producing a greater purchase.

In practice, a bone hole diameter and depth are selected for the material of the bone whereto the suture or sutures are to be attached, taking into account the suture or sutures portion or portions length as will be fitted in the hole and thickness and whether the suture or sutures end portion or portions are knotted, and considering the adhesive to be used. In practice, an adhesive known as polymethylmethacrylate (PMMA), similar to that manufactured by Howmedica, Richards or Zimmer USA, that will dry within approximately one to twenty minutes has been used. Further, a light activate resin as commonly used by dentists can be used as the adhesive for this invention.

The pullout strength or purchase of the mounted suture or sutures that is the resistance to the suture or sutures being pulled out of the mount can be increased when the suture or

sutures end or ends has been knotted. A hole of the invention formed into a bone mass should have a hole wall surface area that is at least equal to the suture or sutures thickness and length of the suture portion that is for positioning in the hole. In practice, this purchase should be the tensile strength of the suture or sutures mounted in the hole.

With the single suture or plurality of sutures end or ends adhesively mounted within the bone hole, the suture or sutures can be used to tie a ligament, or the like, onto that bone surface.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects and features of the invention will become more fully apparent from the following description, in which the invention is described in detail in conjunction with the accompanying drawings. In which drawings:

Fig. 1 is a side elevation view of a section of bone showing straight holes formed into the bone cortex utilizing an awl or k-wire, twist drill and twist drill with a countersinking collar;

Fig. 2 is a view like that of Fig. 1, with the formed holes shown as receiving a tool fitted therein wherever are positioned single suture, plurality of sutures and a plurality of sutures knotted together;

Fig. 3 is a view like that of Fig 2, showing the formed holes with the tools removed and an adhesive filling the individual holes;

Fig. 4 is a side elevation view of a section of bone material with a shallow broad hole formed therein that a knotted section or portion of a pair of sutures has been fitted into, with the hole shown filled with an adhesive;

Fig. 5 is a side elevation view of a section of bone material showing a deep narrow hole formed therein wherein a knotted end portion of a single suture has been positioned and showing the hole filled with an adhesive;

Fig. 6 is a side elevation view of a section of bone material wherein a narrow hole has been formed that is deeper than the hole of Fig. 5, and contains a straight end section or portion of a single suture fitted therein and showing the hole filled with an adhesive;

Fig. 7A is a side elevation view of a scissoring twist drill shown drilling a straight hole into a section of bone material;

Fig. 7B is a view like that of Fig. 7A except a collar portion of the scissoring twist drill is shown as having traveled upwardly along a drill shaft with the upper ends of reaming arms of the drill shown scissoring outwardly and skirt cutting elements of the drill shown extending outwardly to form a hole in the bone material that has an outwardly flared interior wall;

Fig. 7C is a view like that of Fig. 7B with the collar shown returned to the attitude shown in Fig. 7A, closing the

reaming arms showing the scissoring twist drill being pulled out of the formed hole; and

Fig. 8 is a view of the hole formed in the bone material utilizing the scissoring twist drill of Figs. 7A, 7B and 7C, showing a knotted end of a single suture positioned therein and showing the hole filled with an adhesive.

DETAILED DESCRIPTION

Figs. 1, 2 and 3 show a side elevation view of a section of bone material 10 wherein, as shown in Fig. 1, holes are formed into the bone material as by utilizing an awl or k-wire 11, turning a twist drill 12 and twist drill with countersinking collar 13, forming straight holes 14, 15 and 16, respectively. Fig. 2 shows the holes 14, 15 and 16 as having received, respectively, a straight suture 17, a pair of sutures 18 twisted together and a pair of sutures 19 that have a knot 20 tied therein. The single and twisted pair of sutures 17 and 18, respectively, are shown fitted into the respective holes 14 and 15 by folding forward sections of each over an end of a straight insertion rod 21. Which insertion rod includes parallel forward end sections 22 with a space or gap 23 therebetween wherein the suture or sutures are maintained. After, the insertion rod 21 is withdrawn, the folds of the suture 17 and sutures 18 remain in the holes 14 and 15, as shown in Fig. 3. Shown in Fig. 2 the sutures 19 are folded back upon themselves at knot 20, providing sufficient rigidity

to allow the suture knot to be slid by an operator into the hole 16.

With the respective suture 17, sutures 18 and knot 20 of sutures 19 fitted into the prepared holes 14, 15 and 16, shown in Fig. 2, and after removal of insertion rod 21, the holes 14, 15 and 16 are filled with an adhesive 24, as shown in Fig. 3. The adhesive is selected to provide, after curing, for maintaining the suture or sutures in the holes 14, 15 and 16, respectively, to withstand a tensile stress as it is anticipated will be exerted thereon. Which tensile stress is at least a stress as would be exerted on the mounting when the suture or sutures are used to connect a ligament, tendon or soft tissue onto the bone surface, or a like use. In practice, to provide which desired pullout strength or purchase, adhesive 24 is selected to be both easily applied and quick curing. An adhesive known as polymethylmethacrylate (PMMA), has been used successively for practicing this procedure, though, it should be understood, the invention is not limited to use of such material and any adhesive material as is suitable for implantation in a human body, such as a grout filling, other adhesive, bone paste, bone plug, light activated resin as used in dental procedures, or the like, can be so used within the scope of this disclosure.

Figs. 7A, 7B and 7C show a scissoring twist drill 30 as an example of a device for use for forming an inwardly flared or skirt shaped hole 31 in a bone material 29, as shown in Fig. 8.

The hole 31, like the above described holes 14, 15 and 16, is to receive a suture or sutures, shown as a single suture 32 in Fig. 8. The suture 32 can, but is not required to have, a knot 33 tied in an end thereof, or the like, and is fitted in the hole 31 to receive an adhesive 34 therearound that fills hole 31 and, when cured, secures the suture 32 in the bone material 29.

The scissoring twist drill 30, shown in use in Figs. 7A, 7B and 7C, as set out herein, is an example of a drill type device for forming an inverted counter bore or skirt shaped hole 31 for use as set out above. It should, however, be understood that other arrangements for forming a hole like hole 31 into bone material 29 could be so used within the scope of this disclosure. To provide for drilling the hole 31 the scissoring twist drill 30 is for fitting in and being turned by a conventional drill, or the like.

As shown, the scissoring twist drill 30 includes a straight center shaft 35 therethrough that ends in a twist drill end 35a and is for turning, as shown, into bone material 29. Above the twist drill end 35a, a pair of scissor blades 36a and 36b are mounted to the straight center shaft 35 at pivot 37 to scissor apart. In which blade scissoring, lower cutting ends 38a and 38b and upper camming ends 39a and 39b of the respective scissor blades 36a and 36b spread apart and extend out from and are to be retracted back into the straight center shaft 35. Which scissoring action provides for moving

the cutting ends 38a and 38b outwardly to the attitude shown in Fig. 7B. The extended cutting ends of the turning drill 30 ream the hole 31 walls of to the shape shown in Figs. 7B, 7C and 8, when the camming ends 39a and 39b are spread apart. With, when the camming blades are moved together, as shown in Figs. 7A and 7C, the cutting ends 38a and 38b are retracted into the straight shaft 35. To provide for which camming blades travel, the camming blades each include an outwardly slopping surface 40a and 40b, respectively, from a narrow rounded top end 41a and 41b, to an inwardly stepped section, respectively. The camming blades top ends 41a and 41b maintain the scissoring blades in a retracted attitude shown in Figs 7A and 7C, so long as a first sleeve 42 is fitted thereover. The sleeve 42 is preferably biased by a spring, not shown, to resist positioning over the camming blade top ends. To extend or outwardly pivot the scissoring blades cutting ends 38a and 38b, to the altitude shown in Fig. 7B, a second sleeve 43 is journaled to the straight shaft to remain stationary as the straight shaft is turned and, engages the first sleeve 42 that moves over the camming blade top ends 41a and 41b, as shown in Figs. 7A and 7C. To control which second sleeve 43, a handle 44 is fitted to extend out from the second sleeve surface to be held by an operator, who manually retracts the first sleeve 42 telescoping into the second sleeve 43, allowing the camming ends 38a and 38b to spread apart as shown in Fig. 7B.

In practice, for forming hole 31, an operator holding the handle 44 in one hand and the sleeve 42 in their other, as shown in Fig. 7A and drills into the bone material 29. At a desired depth, the operator holding on the handle 44, pulls the first sleeve 42 into the second sleeve 43 allowing the scissoring blades camming ends 39a and 39b to move outwardly that also pivot the scissoring blade cutting ends 38a and 38b outwardly. The cutting ends are thereby moved the attitude shown in Fig. 7B, reaming out the hole 31 to have an inverted counterbore or skirted top portion, as shown best in Fig. 8. Thereafter, to remove the twist drill after hole 31 is formed, holding handle 44, the first sleeve 42 is moved out of the second sleeve 43, traveling over the scissor blade camming ends 39a and 39b, to pivot the scissoring blades 36a and 36b back into the straight shaft 35. With the scissoring blades retracted, as shown in Fig. 7C, the twist drill 30 drill end 35a can be pulled out of the formed hole 31. Which hole 31 then receives, as set out above, a suture end portion and an adhesive to mount that suture end portion in the hole 31 in bone material 29.

Figs. 4, 5 and 6 are here provided to illustrate a relationship between suture configuration and hole dimensions for providing a required purchase of the suture that is mounted to the bone material of the invention. In practice, where a suture is to be used for securing a tendon, ligament, or the like, onto a bone surface, a pull out strength greater than the

yield strength of the suture is preferred. Which purchase is a function of the adhesive properties of a selected adhesive 52, the surface area of the wall of a hole formed into the bone and the surface area of the portion of a suture or sutures fitted in the hole that is covered by the adhesive after curing. Fig. 4 illustrates how a shallow hole 51 formed into bone material 50 can provide a required purchase to a plurality of sutures that have been tied into a knot that is arranged in the hole 51. For the suture mounting of Fig. 4, an adhesive material 52, like that set out above as adhesive 24 known as polymethylmethacrylate or ornoacralate, light activated resin, or the like, can be used. To compute the purchase as will be obtained for this adhesive 52 the hole 51 is formed to have a diameter, shown as d , and height h , to provide a wall area (A_w) having a surface area that is greater than or equal to the suture surface area (A_s) of the portion of the suture that is in the hole. To provide a required and greater purchase or pullout strength. For Fig. 4, the suture surface area (A_s) is the combined thickness of sutures 53 and further includes, at least the surface area of a knot 54 (A_k) computed utilizing the knot 54 diameter K_d . Which knot 54 has been tied in the sutures 53. The knot 54, in practice, effects a column of the cured adhesive 52 and thereby is believed to further increases purchase over the purchase obtained considering the suture and knot surface areas alone.

To further illustrate a relationship between the hole dimensions and suture or sutures, Fig. 5 shows a single suture 56 positioned in a hole 55 that is narrower, shown as diameter d , with a greater height, shown as h , than the hole 51 of Fig. 4. A knot 57 is shown tied in the suture 56 end for further increasing purchase. For calculating purchase of the suture 56 in the hole 55, after curing of adhesive 52 therein, the hole area in relation to the suture and knot surface areas are considered, as set out above, with the presence of knot 57 increasing purchase.

The relationship of hole wall surface area and the suture surface area, as set out above, is taken into consideration to provide at least a required purchase using an adhesive 52, as shown in Fig. -6. Shown therein, a narrow hole 58, shown as having a diameter d , and has a greater height, h , than the height of holes 51 and 55 of Figs. 4 and 5, is provided for mounting a single suture 59 therein. Which suture 59, as shown, does not have a knot, or the like, formed in the end thereof. So arranged, as the suture 59 lacks a knot, additional purchase as such knot would provide is not available, and the purchase is calculated from the relationship of the hole wall area and suture surface area only.

While preferred embodiments of the present invention in a suture mounting system and process have been shown and described herein, it should be apparent that this disclosure is made by way of example only and that variations to both the

suture mountings and processes are possible within the scope of this disclosure without departing from the subject matter coming within the scope of the following claims and a reasonable equivalency thereof, which claims we regard as our invention.

THE CLAIMS

We Claim:

1. A suture anchor system comprising, at least one suture means having a straight end section; a hole formed into a bone material whereat said suture means is to be attached, said hole having an interior surface area that, as relating to a surface area of said suture means straight end section fitted within said hole, is sufficient for preventing said suture means from being pulled from said hole when a tensile force is applied thereto when said hole is filled with an adhesive; and an adhesive suitable for implantation in a human body that, when cured, adheres to or interdigitates into the surfaces of both said suture means straight end section and bone hole interior, forming a bond therebetween.

2. A suture anchor system as recited in Claim 1, wherein the suture means is a single suture having a straight end section for fitting in the bone hole.

3. A suture anchor system as recited in Claim 2, wherein the single suture is bent upon itself, and said suture bend is fitted into the bone hole.

4. A suture anchor system as recited in Claim 2, wherein a knot is formed in the single suture straight end section that is for fitting in the bone hole.

5. A suture anchor system as recited in Claim 1, wherein the suture means is a pair of sutures.

6. A suture anchor system as recited in Claim 5, wherein the pair of sutures are twisted or braided together.

7. A suture anchor system as recited in Claim 5, wherein the pair of sutures are bent upon themselves, and said pair of sutures bend is fitted into the bone hole.

8. A suture anchor system as recited in Claim 5, wherein a knot is tied in an end section of said pair of sutures for fitting into the bone hole.

9. A suture anchor system as recited in Claim 1, wherein the bone hole is formed to have a surface area that is at least equal to the surface area of the section of the suture means installed therein.

10. A suture anchor system as recited in Claim 9, wherein the bone hole contains an entry diameter which is smaller than a wall diameter within said bone hole.

11. A suture anchor system as recited in Claim 1, wherein the adhesive is any biocompatible bone cement or adhesive.

12. A suture anchor system as recited in Claim 1, wherein the adhesive is a light cured resin.

13. A process for anchoring at least one suture to a bone section consisting of, forming a hole into a bone material that is of a diameter and depth to provide an inner wall surface area that is at least equal to the surface area of a section of a suture fitted therein; positioning a section of at least one suture in said formed hole; and filling said suture containing hole with an adhesive material.

14. A process as recited in Claim 13, further including forming the hole into a bone material to have an outwardly sloping portion.

15. A process as recited in Claim 13, wherein an end section of the suture is folded upon itself and said fold is fitted into the hole.

16. A process as recited in Claim 13, further including forming a knot in the end section of the suture that is fitted into the hole.

17. A process as recited in Claim 13, wherein a plurality of sutures are twisted or braided together.

18. A process as recited in Claim 17, wherein an end section of the plurality of sutures is folded upon itself and said fold is fitted into the hole.

19. A process as recited in Claim 17, further including forming a knot in a section of the plurality of sutures that is fitted into the hole.

20. A process as recited in Claim 13, wherein the adhesive material is any biocompatible bone cement, resin or crnoacralate.

21. A process as recited in Claim 12, where the adhesive material is a grout, filling adhesive, bone paste, bone plug, or light activated resin material suitable for implantation in a human body.





FIG. 2




FIG. 3




FIG. 4




FIG. 5








FIG. 6





PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61B 17/00	A3	(11) International Publication Number: WO 97/10743 (43) International Publication Date: 27 March 1997 (27.03.97)
(21) International Application Number: PCT/IB96/01298 (22) International Filing Date: 17 September 1996 (17.09.96) (30) Priority Data: 08/531,780 21 September 1995 (21.09.95) US (71) Applicant: MEDICINELODGE, INC. [US/US]; 152 South 600 West, Logan, UT 84321 (US). (72) Inventors: CHERVITZ, Alan; 152 South 600 West, Logan, UT 84321 (US). GOBLE, E., Marlowe; 850 East 1200 North, Logan, UT 84341 (US). (74) Agent: RUSSELL, M., Reid; Suite 300, 261 East 300 South, Salt Lake City, UT 84111 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> (88) Date of publication of the international search report: 17 April 1997 (17.04.97)

(54) Title: SUTURE ANCHOR SYSTEM AND METHOD

(57) Abstract

This invention is a suture anchor system for securing a suture (17)(18)(19), into a bone cortex (10) surface. The system includes forming a hole (14)(15)(16) into a bone cortex surface that is of a diameter and depth to provide a wall surface area that is at least as great as the surface area of an end section of a suture or sutures fitted therein. By filling the hole with an adhesive (24) that is allowed to cure, a suture mounting is provided that will have a pullout strength or purchase that is greater than a load as is anticipated to be applied thereto. To increase the purchase a portion of the hole formed into the bone cortex may be counter bored to form an outwardly extending skirt, the suture may be folded upon itself, a knot may be tied in the suture, or a pair of sutures can be combined together.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB96/01298

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : A61B 17/00

US CL : 606/232

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : Please See Extra Sheet.

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4,696,301 A (BARABE) 29 September 1987, entire document.	1, 2, 11, 12



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z*	document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means		
P document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

13 FEBRUARY 1997

Date of mailing of the international search report

07 MAR 1997

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3590

Authorized officer

JEFFREY A. SCHMIDT

Telephone No. (703) 308-0859

INTERNATIONAL SEARCH REPORT

International application No.
PCT/IB96/01298

B. FIELDS SEARCHED

Minimum documentation searched

Classification System: U.S.

433/228.1, 48; 523/116; 606/60, 73, 75, 92-95, 104, 187, 232; 623/13